

BLADE SNOWSTORM SPECIFICATIONS



Made In America,
By America

The Blade SS

For Machines in weight range of 14,500 lbs – 30,000 lbs	KBSS 10'	KBSS 12'	KBSS 14'
Machine Size Rec.	14.5K – 30K	18K – 30K	19K – 30K
Angle	36 Degrees		
Blade Width	10'	12'	14'
Blade Width at Full Angle	97"	116.5"	136"
Oscillation (Degrees/Inches) Each End	6° / 12.5"	6° / 15"	6° / 17.5"
Moldboard Gauge / Steel Grade	10 ga. / Grade 50		
SnowKage XL Hydro Lock Bracket Kit	Optional		
Loader Attachment	Most Quick Attach Styles		
Trip Springs	8 Compression		
Cutting Edge	(2) 5/8" x 8" x 5' High Carbon	(2) 5/8" x 8" x 6' High Carbon	(2) 5/8" x 8" x 7' High Carbon
Hydraulic Crossover Relief Valve	Standard		
Pivot Frame Length for Loader Attachment (from attachment point to plow angle hinge point)	48"		
Weight	2282 lb	2,375 lb	2,468 lb
Cylinders	(2) 3" Bore 1 1/2" Rod		
Blade Height	36"		
Hydro Lock Kit	Optional	Optional	Optional
Electric / Hydraulic Valve Kit (required if 2nd auxiliary function is not available)	Optional	Optional	Optional



Manufactured By:

Kage Innovation LLC

22200 Meadowbrook Ave. N

Scandia, MN 55073

651 433 4628

www.kageinnovation.com

Email: info@kageinnovation.com

©2010 Kage Innovation LLC

Kage Innovation reserves the right to make changes to improve product



The SnowKage SS

For Machines in weight range of 15,000 lbs – 30,000 lbs	SKSS 10'	SKSS 12'	SKSS 14'
Machine Size Rec.	15K – 30K	18K – 30K	19K – 30K
Height Of Box	41"		
Overall Width	143"	155"	167"
Overall Width At Full Angle	122"	141"	160"
Polyurethane Skids	2" x 10" x 42"	2" x 10" x 42"	2" x 10" x 42"
Approx. Capacity	12 yd +	14 yd +	18 yd +
Total Weight of System (Blade & Box)	3,088 lb	3,181 lb	3,274 lb



Manufactured By:

Kage Innovation LLC

22200 Meadowbrook Ave. N

Scandia, MN 55073

651 433 4628

www.kageinnovation.com

Email: info@kageinnovation.com